



## Installation Instructions

<b>Model:</b>	Polaris General
<b>Description:</b>	Rear Pods Install
<b>Part Number:</b>	MBQG-RPOD-1
<b>Assembly Time:</b>	45 Min

Before you begin, read through these instructions and check that all parts are present. Always disconnect negative battery terminal prior to installation. Please note that MB Quart cannot assume any responsibility for damage resulting from incorrect installation.

Parts List		
No.	Component Name	Qty
1	6.5" Rear Pod Speakers (MBQG-RPOD-1)	2

Tools Required	
1	13mm Wrench
2	4mm & 5mm Allen Wrench

## Rear Speaker Install

### NOTE

If you have a MB Quart Stage 3 kit then proceed. If you are adding the rear speakers to any other audio system run wires to your amplifier location

- Attach the left and right harness to bullet connectors in the center console and then route these to the left and right side of the vehicle staying clear of moving and hot parts



- Install speaker to bracket with four M6 Button head bolts using a 4mm Allen wrench, then position bracket on the ROPS with four M8 bolts, eight M8 washer, and four M8 locknuts securing with a 5mm Allen wrench and 13mm socket



- Inside bracket should have groove facing toward center of vehicle



## Rear Speaker Install

- Connect wiring





#### FCC Notice

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a mobile installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

WARNING: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment complied with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

#### WARRANTY

Maxxsonics USA Inc. warrants this product, to the original consumer purchaser, to be free from defects in material and workmanship for a period of one (1) year from the date of purchase. Maxxsonics USA Inc. will, at its discretion, repair or replace defective products during the warranty period. Components that prove to be defective in materials and workmanship under proper installation and use must be returned to the original authorized Maxxsonics USA Inc. retailer from where it was purchased. A photocopy of the original receipt must accompany the product being returned. The costs associated with removal, re-installation and freight are not the responsibility of Maxxsonics USA Inc. This warranty is limited to defective parts and specifically excludes any incidental or consequential damages connected therewith. To view the full warranty, please visit the website.

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use such marks by MB Quart is under license.

All product names, logos, and brands are property of their respective owners. All company, product and service names used in this literature are for identification purposes only. Use of these names, logos, and brands does not imply endorsement.

©2021 Maxxsonics USA, Inc.

MBQuart products are designed and engineered in the USA by



MBQG-RPOD-1 REV 01